



1. A recent survey showed CAD/CAM scanners used for outsourcing are expected to grow by:
 - a. 10 percent.
 - b. 20 percent.
 - c. 30 percent.
 - d. 40 percent.
2. The frame modifier is applied in a layer of approximately
 - a. .1mm
 - b. .5mm
 - c. 1mm
 - d. 1.5mm
3. The preliminary bake consisted of ODM-1 on the underside of the pontic to prevent an increasing of the value.
 - a. True
 - b. False
4. A highly fluorescent transparent porcelain allows you to influence color and depth.
 - a. True
 - b. False
5. An overlay of E58 Enamel and EOP3 was used in the mesial and distal lobes.
 - a. True
 - b. False
6. To mimic natural dentition, the author used:
 - a. EO 15 and 17
 - b. EO 16 and 17
 - c. EO 15 and 16
 - d. EO 17 only
7. The second bake consisted of CT 23 and a combination of TN and TN+EOP3.
 - a. True
 - b. False
8. Surface texture can be addressed before contours are finalized.
 - a. True
 - b. False
9. To obtain a luster, you can use a luster paste instead of glaze?
 - a. True
 - b. False
10. Firing should be done to your requirements not the manufacturer's instructions.
 - a. True
 - b. False

Passing quiz grades are worth ½ point documented scientific credit. Quiz results will appear on the NBC CDT Online Education Tracking System at www.nadl.org under the Certification Section, which is updated on or around the 15th of every month. Once completed, send your quiz to the National Board for Certification in Dental Laboratory Technology at the address or fax number below. Name: _____ CDT #: _____ Date: _____ 325 John Knox Rd, Suite L103, Tallahassee, Florida 32303 (850) 222-0053 FAX This quiz is provided to test the technician's comprehension of the article's content, and does not necessarily serve as an endorsement of the content by NADL or NBC.